



US
163-153
MT

Copyright Log





ENERPAC
 POWERED SOLUTIONS. GLOBAL FORCE.

Instruction Sheet
 Hydraulic Maintenance Site

1. Safety
 2. Pre-Use Inspection
 3. Operation
 4. Maintenance
 5. Storage

IMPORTANT SAFETY INSTRUCTIONS

1. Read and understand all instructions before using this tool.
 2. Do not use this tool if you are under the influence of alcohol, drugs, or medication.
 3. Do not use this tool if you are fatigued or tired.
 4. Do not use this tool if you are wearing loose clothing or jewelry.
 5. Do not use this tool if you are wearing safety glasses or eye protection.
 6. Do not use this tool if you are wearing a hard hat or other head protection.
 7. Do not use this tool if you are wearing a seat belt or other safety harness.
 8. Do not use this tool if you are wearing a safety vest or other safety gear.
 9. Do not use this tool if you are wearing a safety helmet or other safety gear.
 10. Do not use this tool if you are wearing a safety harness or other safety gear.

Weight	11.0
Height	16.0
Width	16.0
Depth	16.0
Volume	16.0
Capacity	16.0
Pressure	16.0
Flow Rate	16.0
Temperature	16.0
Humidity	16.0
Altitude	16.0
Latitude	16.0
Longitude	16.0

ENERPAC
 POWERED SOLUTIONS. GLOBAL FORCE.

Maintainance Chart / USE 10 BALL CHARGES
 5 TON
 Maximum Pressure: 1000 PSI

HEALTHY
 10
 SPACING

Diagram showing various hydraulic components and their corresponding maintenance instructions.

ENERPAC
POWERFUL SOLUTIONS. GLOBAL FORCE.

5 Ton
Maintenance Set / 1000-10 Kit Contents
Maximum System Pressure: 1000 psi

	Locking Dump Valve		Double Check Valve 1.5\"/>		Ball Valve 1.5\"/>		Lock Pin 1/8\"/>		Adjustment Screw
	Threaded Plug 1.5\"/>		Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Lock Pin 1/8\"/>		Adjustment Screw
	Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Lock Pin 1/8\"/>		Adjustment Screw
	Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Lock Pin 1/8\"/>		Adjustment Screw
	Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Lock Pin 1/8\"/>		Adjustment Screw
	Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Ball Valve 1.5\"/>		Lock Pin 1/8\"/>		Adjustment Screw

For a complete list of parts, please refer to the parts list on the inside of the box. For more information, visit www.enerpac.com.





bremco METAL PRODUCTS
1300 273 626
www.bremco.com.au

EMERGENCY
ASSEMBLY
AREA

WARNING
RESTRICTED
ACCESS

WARNING
RESTRICTED
ACCESS





EMERSON



⚠ WARNING 警告

TO AVOID POSSIBLE SERIOUS PERSONAL INJURY OR DEATH

- Read all instruction sheets before using cylinders and jacks.
- Cylinders or jacks must be fully supported on firm surface capable of supporting the full load. • Load must be centered and cover entire plunger. • Lift only dead weight loads. • Stay clear of lifted loads. • Follow lifted load with cribbing. • Do not use cylinders and jacks if damaged, altered, or in need of repair.
- When extending double acting cylinders the return port must be unrestricted. • Be sure all couplers are completely connected.
- Add oil to pump only when all plungers are completely retracted.
- Use only manufacturer approved hydraulic fluid.

This guide cannot cover every situation, so always follow the instructions with SAFETY first. Use common sense. Read the instructions.

重大事故や人身事故を避けるためにシリンダやジャッキを使用する前に取扱説明書を読んで下さい。シリンダやジャッキは負荷に耐える堅固な面で荷重を支えて下さい。持ち上げるのは静荷重だけです。ジャッキアップの場所から離れて作業して下さい。シリンダやジャッキは損傷がある場合や老朽化して修理の必要があるときはロクを使わないで下さい。複動シリンダを前進させるときは完全側を常にタンクに開放させ下さい。ポンプにオイルを接続されていることを確認して下さい。ポンプにオイルを追加するときはプランジャが完全に戻っていることを確認して下さい。オイルは弊社指定の純正作動油を使用して下さい。この警告ガイドは全ての場合を網羅していません。取扱説明書を良く読んで、常に安全第一を心がけて下さい。

ENERPAC
RC106
MAX 10,000 PSI
MAX 700 BAR
10 TON E1121K



